

1 Amendments to the Claims:

2 This listing of claims will replace all prior versions, and  
3 listings, of claims in the application using (Original) (Currently  
4 Amended) (New) (Canceled) nomenclature, as recited in the below  
5 listing of claims.

6  
7 1. (Currently Amended) A method for retrieving from a destination  
8 web content data specified by a source at a source internet  
9 protocol address (IPA) and corresponding to a uniform resource  
10 locator (URL) associated with a web server, the method comprising  
11 the steps of,

12 storing at a proximal IPA in a forwarding table a destination  
13 IPA,

14 storing at the proximal IPA in the forwarding table a  
15 destination URL identifier for identifying the web content data,  
16 the destination URL identifier is stored in the forwarding table in  
17 reference to the destination IPA,

18 receiving at the proximal IPA from the source a source URL  
19 identifier,

20 matching at the proximal IPA the source URL identifier to the  
21 destination URL identifier,

22 cross referencing at the proximal IPA in the forwarding table  
23 the stored destination URL identifier with the destination IPA, and

24 transmitting from the proximal IPA the destination URL  
25 identifier to the destination at the destination IPA, and for  
26 transmitting from the destination at the destination IPA the web  
27 content data to retrieve the web content data from the destination.

28 ///

1 2. (Original) The method of claim 1 wherein,  
2 the destination is a distal web cache,  
3 the source is a user browser at a source IPA,  
4 the source URL identifier is an exact URL,  
5 the proximal IPA is an IPA of a proximal web cache,  
6 the distal web cache transmits the web content data to the source  
7 at the source IPA,  
8 the method further comprising the steps of  
9 receiving the source IPA at the proximal web cache, and  
10 transmitting the source IPA to the distal web cache, the  
11 distal cache transmitting the web content data to the user browser.  
12

13 3. (Original) The method of claim 1 wherein,  
14 the destination is a distal web cache,  
15 the destination IPA is a distal web cache IPA  
16 the source is a user browser at a source IPA,  
17 the source URL identifier is an exact URL,  
18 the destination URL identifier is an encoded URL,  
19 the proximal IPA is an IPA of a proximal web cache,  
20 the distal web cache transmits the web content data to the proximal  
21 web cache,  
22 the method further comprising the steps of  
23 receiving the source IPA at the proximal web cache,  
24 transmitting the proximal IPA to the distal web cache,  
25 receiving from the distal web cache the web content data at  
26 the proximal web cache, and  
27 transmitting the web content data from the proximal web cache  
28 to the user browser at the source IPA.

1 4. (Original) The method of claim 1 wherein the destination URL  
2 identifier in the forwarding table is a series of compression codes  
3 corresponding to respective linked segments of the URL, each of the  
4 linked segments corresponding to one or more components of the URL  
5 to decompose the URL into the linked segments, the linked segments  
6 are linked by parental pointers from a first linked segment having  
7 no parental pointer through remaining linked segments having  
8 respective parental pointers to a preceding one of the linked  
9 segments to a last linked segment reference to the destination IPA.

10  
11  
12  
13 5. (Currently Amended) The method of claim 4 wherein,  
14 the destination URL identifier references the URL comprising  
15 scheme, name, path and type components and delimiters,  
16 the linked segments correspond to successive concatenated  
17 components of the URL and are respectively referenced to one or  
18 more of the successive concatenated components of the URL,  
19 each of the compression codes are referenced to the linked  
20 segments and to the one or more successive concatenated components  
21 through pointers for respectively cross referencing the compression  
22 codes to the linked segments, and  
23 the destination IPA is referenced to the destination URL  
24 identifier when the all of the respective compression codes through  
25 the respective pointers point to a complete set of linked segments  
26 from the first linked segment to the last linked segment.

27  
28 ///

1 6. (Original) The method of claim 5 wherein,

2 the proximal IPA becomes a new source IPA as the destination  
3 IPA becomes a new proximal IPA communicating the destination URL  
4 identifier to a new destination IPA all of which occurring a  
5 plurality of times for indicating a number of hops from the  
6 proximal IPA to a last one of a respective plurality of new  
7 destination IPAs, the last one of the respective plurality of new  
8 destination IPA distally storing the web content data, and

9 the last linked segment is further referenced to a distance  
10 metric indicating a number of hops through the new destination IPAs  
11 from the proximal IPA.

12  
13 7. (Original) The method of claim 1 wherein,

14 the destination stores a set of web content data one of which  
15 is the web content data, the set of web content data corresponding  
16 to a wildcard URL for indicating a set of URLs one of which is the  
17 URL,

18 the destination URL identifier is a wildcard URL identifier,  
19 the source URL identifier is an exact URL having a plurality of URL  
20 components a first of portion of which serving as a prefix to a  
21 remaining portion of the exact URL, and

22 the matching step is a prefix matching step for matching the  
23 first portion of the URL components of the exact URL to the  
24 wildcard URL identifier in the forwarding table.

25  
26  
27  
28 ///

1 8. (Original) The method of claim 7 wherein,  
2 the prefix matching step is a longest prefix matching step  
3 serving to match the longest first portion of the URL components of  
4 the exact URL to the wildcard URL among a plurality of wildcard  
5 URLs matching a shorter first portion of the URL components of the  
6 exact URL.

7  
8 9. (Currently Amended) A method for retrieving from a distal cache  
9 web content data specified by a user browser at a source internet  
10 protocol address (IPA) and corresponding to a uniform resource  
11 locator (URL) associated with a web server, the method comprising  
12 the steps of,

13 storing at a proximal IPA in a forwarding table a distal IPA,  
14 storing at the proximal IPA in the forwarding table a distal  
15 URL identifier for identifying the web content data, the distal URL  
16 identifier is stored in the forwarding table in reference to the  
17 distal IPA,

18 receiving from the user browser a source URL identifier,  
19 matching at the proximal IPA the source URL identifier to the  
20 distal URL identifier,

21 cross referencing at the proximal IPA in the forwarding table  
22 the stored distal URL identifier with the distal IPA, and

23 transmitting from the proximal IPA the distal URL identifier to  
24 the distal destination at the destination IPA, ~~and~~ for transmitting  
25 from the distal cache at the distal IPA the web content data to  
26 retrieve the web content data from the distal web cache.

27  
28 ///

1 10. (Original) The method of claim 9 wherein the web content data  
2 is transmitted from the distal cache to the user browser during the  
3 transmitting step.

4  
5 11. (Original) The method of claim 9 wherein,  
6 the proximal IPA is a location of a proximal cache,  
7 the web content data is transmitted from the distal cache to  
8 the proximal cache during the transmitting step, and  
9 the web content data is further transmitted from the proximal  
10 cache to the user browser during the transmitting step.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28 ///

12. (Currently Amended) A method for retrieving from a distal web  
cache web content data specified by a user browser at a source  
internet protocol address (IPA) and corresponding to a uniform  
resource locator (URL) associated with a web server, the method  
comprising the steps of,  
storing at a proximal IPA in a forwarding table a distal IPA,  
storing at the proximal IPA in the forwarding table a distal  
URL identifier for identifying the web content data stored in the  
distal cache, the distal URL identifier is stored in the forwarding  
table in reference to the destination IPA,  
receiving at the proximal IPA from the user browser a source  
URL identifier,  
matching at the proximal IPA the source URL identifier to the  
destination URL identifier,  
cross referencing at the proximal IPA in the forwarding table  
the stored distal URL identifier with the destination IPA, and  
transmitting from the proximal IPA the distal URL identifier to  
the destination at the destination IPA, ~~and~~ for transmitting from  
the destination at the destination IPA the web content data for  
retrieving the web content data from the distal cache.

///

1 13. (Currently Amended) The method of claim 12 further comprising  
2 the step of,  
3 repeating all of the steps one or more times, the destination  
4 is one or more intermediate cooperative web caches having a  
5 respective one or more intermediate IPAs and respectively storing  
6 the distal URL identifier with a respective next one of the one or  
7 more intermediate IPAs and lastly the distal IPA, each of the one  
8 or more intermediate IPAs being a location of a next one of the one  
9 or more intermediate cooperative web caches and lastly the distal  
10 IPA, the one or more intermediate IPAs indicating next web hop  
11 locations in transmitting the distal URL through the intermediate  
12 cooperative web caches to the distal web cache, the last one of one  
13 or more intermediate cooperative web caches referencing the distal  
14 URL to the distal IPA for retrieving the web content data from the  
15 distal cache.

16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28 ///



1 14. (Original) The method of claim 13 wherein the repeated  
2 transmitting step,

3 the web content data is transmitting from the distal cache  
4 through the one or more intermediate web caches and through a  
5 proximal cache at the proximal IPA to the user browser.

6  
7  
8  
9 15. (Original) The method of claim 14 further comprising the step  
10 of,

11 assigning the proximal cache and one or more intermediate  
12 caches and the distal cache to one or more groups of cooperative  
13 caches in a network of grouped cooperative web caches, the web  
14 content data being transmitted from a first one of the one or more  
15 intermediate caches to a second one of the one or more intermediate  
16 caches, the first one and second one of the one or more  
17 intermediate caches being within the same group.

18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28 ///